

M POD

QUALITY STANDARDS

- GREENGUARD UL 2818 - 2022 Gold
- Standard for Chemical Emissions
- Class A – > 30lb
- ASTM 565 SGS acoustic test
- E 531267 UL 962
- ISO 3382-2-2008 SGS Reverberation Time Test
- ISO 16001 SGS indoor air test
- ISO 23351-1:2020 SGS acoustic test report-EN
- ASTM E84 Fire rated Class

TECHNICAL INFORMATION

Types

- modular office pod

Exterior

- Painted sheet metal, 10 mm tempered glass with aluminium frames

Carpet

- Anti-static and stain resistance low loop pile carpet for the floor

Walls and roof

- A sandwich element of sheet metal, fire rated gypsum board, recycled acoustic foam and acoustic felt

Glass

- 10 mm safety glass with aluminium frame with sound Control 5 + 5 mm laminated glass door with alu frame, SS lock, handle and pivot hinges

Power consumption

- 19 W while in use (Standard configuration)
 - LED light: 6 W
 - Fans (2 pcs) in total: 12 W
 - 3 m wire

Table outlets

- Power socket, USB, type C, Network cable port

Ventilation

- Total air flow is 309.82 m³/h, air replaced every 1.12 min

Lighting

- Inductive LED light: 4000 K

Dimensions

- Exterior: 2200 mm x 1200 mm x 2320 mm (width, depth, height)
- Interior: 2078 mm x 1078 mm x 2170 mm (width, depth, height)
- Doorway: 840 mm width

Furniture

- Sofa 1070 mm x 580 mm x 680 mm (width, length, height)
- Table 500 mm x 700 mm x 680 mm (width, length, height)